

Declaration of Performance refer to CPR 305/2011

EN

1 DoP Reference number	BM / G1 / 1005		
2 Product-Code	ACO Therm Leibungsrahmen mit Kippfenster 14mm Verglasung		
3 Product specification: (Numbers or Specification of product)	See label on the product		
4 Intended use	Windows and external pedestrian doorsets without resistance to fire and/or smoke leakage characteristics		
5 Manufacturer	ACO Severin Ahlmann GmbH & Co. KG Am Ahlmannkai D-24782 Büdelsdorf		
6 Authorised representative	Not relevant		
7 Assessment and verification of constancy of performance	System 3		
8 Relevant harmonised standard	EN 14351-1:2006		
9 First year of CE marking	2010		
10 Notified body	ift Rosenheim 0757		
11 Type test report reference number	ift 102 38 156 / 3		
12 Essential characteristics	Performance declared		
		Kipp	
Resistance to wind load		C1/B1	
Water tightness		Cl. 2A	
Air permeability		Cl. 1	
Thermal transmittance U_w W/(m ² K)		3,0 W/(m ² K)	
Acoustic performance		npd	
Load-bearing capacity of safety device		npd	
Dangerous substances		npd	
Protection against burglary		npd	
g – Value		0,77	
Light transmittance		0,82	
13 Specific technical documentation (article 37/38)	Installation guideline		
14 Other information	–		

npd = no performance determined (engl.) = Leistungsmerkmale nicht festgelegt (deutsch)

The performance of the product(s) identified in points 2 and 3 is in conformity with the declared performance in point 12. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5. Signed for and on behalf of the Manufacturer by

Rendsburg/Büdelsdorf, October 2013



Hartmut Jennrich, sales department
ACO Severin Ahlmann GmbH & Co. KG

