



UE Nº 305/2011 Regulation Declaration of Performance

1. DoP Reference Number:

2. Product Description:

3. Product Serial Number(s):

4. Intended use:

5. Manufacturer:

6. Authorised Representative:

7. Assessment and verification of constancy of performance:

8. Relevant Harmonised Standard:

9. First year of CE Marking:

10. Notified Body that performed Type Test:

11. Type Test Report Reference No.:

12. Essential Characteristics:

ED/SP/0012

ACO DRAIN® N 100 to N 200

 $0000003,\,00000011,\,00000023,\,00000034,\,0000039,\,0000040,\,00000701-\\00000703,\,00000711-00000713,\,00000721-00000723,\,00000731-00000733,\\00001659,\,00001661-00001663,\,00002872-00002874,\,00002882-00002884,\\00002892-00002894,\,00003093-00003095,\,000X3096-000X3098,\,C0000099-\\C0000118,\,C0000617,\,C0000618$

Drainage channel system type M for collection and conveyance of surface water from areas subject to pedestrian and/or vehicular traffic.

ACO Productos Polímeros, S.A.U. Pol. Ind. Puigtió, Ap. Correos 84, 17412 Maçanet de la Selva (Girona), Spain Not applicable

System 3

UNE EN 1433:2003

Annex ZA

2006 1502

Hansa-Nord Labor

für bautechnische Prüfungen Flensburger Strasse, 15 D-25421 Pinneberg

Nord Labor 2/173.4/2006, Nord Labor 2/173.6/2006, Nord Labor

2/173.7/2006, Nord Labor 2/388.10/2011, Nord Labor

2/692.2/2006

Characteristic Performance/Results

Load Class A15 to C250 providing that the installation instructions are observed

Water-tightness No leakage

Durability Flexural Strength:
3 samples average value>=22 N/mm2;
Lower individual value>=18 N/mm2

Compressive Strength:
3 samples average value>=90 N/mm2;
Lower individual value>=75 N/mm2

13. Specific Technical Documentation: Not applicable

The performance of the product(s) identified in points 2 and 3 is in conformity with the declared performance in point 12. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5. Signed for and on behalf of the Manufacturer by:

Maçanet de la Selva, 2013

X. Pascual / Operations Manager

^{*}Maximum Load Class when used in combination with A15 to C250 providing that the installation instructions are observed gatings only