



Declaration of Performance according to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/5027		
2 Product description	Separator for light liquids Oleopator-C-NST-HPC-LLT		
3 Product specification: (Numbers or Specification of product)	Oleopator-C-NST-HPC-LLT NS (x) (see following page)		
4 Intended use	Light liquid removal from wastewater to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
9 First year of CE marking	2023		
10 Notified body	Irrelevant		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 858-1	Performance
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 21.07.2023

Dennis Papadopoulos
Managing Director





Declaration of Performance according to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt 23
DIN EN 858-1:2005 separator systems for light liquids Oleopator-C-NST-HPC-LLT class I Material: concrete Installation parts: PE-HD

Overview of the CE marked separator systems for light liquids Type Oleopator-C-NST-HPC-LLT

NS (x)	Oil storage capacity (l)	Ø D (mm)
15	464	1500
20	594	1500
30	654	1500
40	1350	2200
50	1350	2200
65	1674	2200
80	2216	2200
100	2216	2200

