



## Declaration of Performance refer to EU BauPVO 305/2011

<b>1 DoP Reference number</b>	ST/G1/5001		
<b>2 Product description</b>	Separator for light liquids Oleosmart		
<b>3 Product specification: (Numbers or Specification of product)</b>	Oleosmart NS x SF y (see following page)		
<b>4 Intended use</b>	Light liquid removal from waste water to protect drainage systems and surface water		
<b>5 Manufacturer</b>	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
<b>6 Authorised representative</b>	Irrelevant		
<b>7 Assessment and verification of constancy of performance</b>	System 3 and System 4		
<b>8 Relevant harmonised standard</b>	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
<b>9 First year of CE marking</b>	2010		
<b>10 Notified body</b>	System 3 – Reaction to fire: NB-Nr. 1508		
<b>11 Type test report reference number</b>	Irrelevant		
<b>12 Essential characteristics</b>	<b>Main features</b>	<b>DIN EN 858-1</b>	<b>Performance</b>
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
	Durability	6.2	pass
<b>13 Specific technical documentation (article 37/38)</b>	Installation manual		
<b>14 Other information</b>	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12.  
The manufacturer only is responsible for the creation of this declaration of performance according to No. 5.  
Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013


Sven Schrothe  
Managing Director





## Declaration of Performance refer to EU BauPVO 305/2011

### Information accompanying the CE marking

	
ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt	
10	
DIN EN 858-1	
separator systems for light liquids Oleosmart class I with integrated sludge trap	
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD	

### Overview of the CE marked separator systems for light liquids Type Oleosmart

NS (x)	SF (y)	Oil storage capacity (l)	Ø D (mm)
4	400	142	1000
4	800	211	1200
6	600	396	1500
6	1200	396	1500
10	1000	396	1500
10	2000	396	1500
15	1500	744	2200
10-15	3000	744	2200
6-15	5000	744	2200

