



Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/5004		
2 Product description	Separator for light liquids Oleomax		
3 Product specification: (Numbers or Specification of product)	Oleomax NS x SF y (see following page)		
4 Intended use	Light liquid removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
9 First year of CE marking	2006		
10 Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 858-1	Performance
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
06
DIN EN 858-1
separator systems for light liquids Oleomax class II with integrated sludge trap
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD

Overview of the CE marked separator systems for light liquids Type Oleomax

NS (x)	SF (y)	Sludge trap- volume (l)	Oil storage capacity (l)	Ø D (mm)
3	300	180	163	1000
3	600	440	163	1000
3 TVO	600	310	506	1000
4	800	420	160	1000
4 TVO	800	400	453	1000
6	1200	588	160	1000
6 TVO	1200	650	512	1200
6	1800	901	576	1500
6	2500	1255	576	1500
6	5000	2500	797	1500
8	1600	901	576	1500
8	2400	1255	576	1500
8	2500	1255	576	1500
8	5000	2500	798	1500





Declaration of Performance refer to EU BauPVO 305/2011

NS (x)	SF (y)	Sludge trap-volume (l)	Oil storage capacity (l)	Ø D (mm)
10	2000	1997	576	1500
10	2500	2520	576	1500
10	5000	2500	798	1750
15	3000	1650	1163	2200
15	5000	2450	1163	2200
20	2000	1000	1163	2200
20	4000	2000	1163	2200
20	5000	2450	1163	2200
20	6000	3000	1163	2200
30	3000	3190	1513	2200
30	5000	4980	1513	2200
30	6000	5830	1513	2200

