



Declaration of Performance refer to EU BauPVO 305/2011

| | | | |
|---|---|------------------------------|--------------------|
| 1 DoP Reference number | ST/G1/5005 | | |
| 2 Product description | Separator for light liquids Oleopator | | |
| 3 Product specification: (Numbers or Specification of product) | Oleopator NS x SF y (see following page) | | |
| 4 Intended use | Light liquid removal from waste water to protect drainage systems and surface water | | |
| 5 Manufacturer | ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt | | |
| 6 Authorised representative | Irrelevant | | |
| 7 Assessment and verification of constancy of performance | System 3 and System 4 | | |
| 8 Relevant harmonised standard | DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007 | | |
| 9 First year of CE marking | 2006 | | |
| 10 Notified body | System 3 – Reaction to fire: NB-Nr. 1508 | | |
| 11 Type test report reference number | Irrelevant | | |
| 12 Essential characteristics | Main features | DIN EN 858-1 | Performance |
| | Reaction to fire | 6.2.8 | E |
| | Fluid resistant | 6.3.2 | pass |
| | Effectiveness | 4, 6.3.1, 6.3.3 – 6.3.8, 6.5 | pass |
| | Load-bearing capacity | 6.4 | pass |
| Durability | 6.2 | pass | |
| 13 Specific technical documentation (article 37/38) | Installation manual | | |
| 14 Other information | – | | |

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

| |
|---|
| |
| ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt |
| 06 |
| DIN EN 858-1 |
| separator systems for light liquids Oleopator class I with integrated sludge trap |
| Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD |

Overview of the CE marked separator systems for light liquids Type Oleopator

| NS (x) | SF (y) | Oil storage capacity (l) | Ø D (mm) |
|--------|--------|--------------------------|----------|
| 1,5 | 150 | 163 | 1000 |
| 3 | 300 | 163 | 1000 |
| 3 TVO | 300 | 512 | 1000 |
| 3 | 600 | 163 | 1000 |
| 3 TVO | 900 | 464 | 1200 |
| 4 | 400 | 160 | 1000 |
| 4 TVO | 400 | 453 | 1000 |
| 4 TVO | 800 | 512 | 1200 |
| 4 | 1200 | 236 | 1200 |
| 4 TVO | 1200 | 576 | 1500 |
| 6 | 600 | 160 | 1000 |
| 6 TVO | 600 | 512 | 1200 |
| 6 | 1200 | 236 | 1200 |
| 6 | 1800 | 576 | 1500 |
| 6 | 2500 | 576 | 1500 |
| 6 | 5000 | 1272 | 2200 |





Declaration of Performance refer to EU BauPVO 305/2011

| NS (x) | SF (y) | Oil storage capacity (l) | Ø D (mm) |
|--------|--------|--------------------------|----------|
| 8 | 800 | 273 | 1500 |
| 8 | 1600 | 576 | 1500 |
| 8-10 | 1000 | 273 | 1200 |
| 8 | 2400 | 576 | 1500 |
| 10 | 2000 | 576 | 1500 |
| 8-10 | 2500 | 576 | 1500 |
| 10 | 3000 | 576 | 1500 |
| 8-10 | 5000 | 1272 | 2200 |
| 15 | 1500 | 464 | 1500 |
| 15 | 3000 | 464 | 1500 |
| 15 | 5000 | 1163 | 2200 |
| 20 | 2000 | 594 | 1500 |
| 20 | 4000 | 1163 | 2200 |
| 20 | 5000 | 1163 | 2200 |
| 20 | 6000 | 1163 | 2200 |
| 30 | 3000 | 1513 | 2200 |
| 30 | 5000 | 1513 | 2200 |
| 30 | 6000 | 1513 | 2200 |
| 40 | 4000 | 1350 | 2200 |
| 40 | 5000 | 1350 | 2200 |
| 50 | 5000 | 1350 | 2200 |

