



## Declaration of Performance refer to EU BauPVO 305/2011

<b>1 DoP Reference number</b>	ST/G1/5006		
<b>2 Product description</b>	Separator for light liquids Oleopator		
<b>3 Product specification: (Numbers or Specification of product)</b>	Oleopator NS x SF y (see following page)		
<b>4 Intended use</b>	Light liquid removal from waste water to protect drainage systems and surface water		
<b>5 Manufacturer</b>	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
<b>6 Authorised representative</b>	Irrelevant		
<b>7 Assessment and verification of constancy of performance</b>	System 3 and System 4		
<b>8 Relevant harmonised standard</b>	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
<b>9 First year of CE marking</b>	2006		
<b>10 Notified body</b>	System 3 – Reaction to fire: NB-Nr. 1508		
<b>11 Type test report reference number</b>	Irrelevant		
<b>12 Essential characteristics</b>	<b>Main features</b>	<b>DIN EN 858-1</b>	<b>Performance</b>
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
<b>13 Specific technical documentation (article 37/38)</b>	Installation manual		
<b>14 Other information</b>	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe  
Managing Director





**Declaration of Performance refer to EU BauPVO 305/2011**

**Information accompanying the CE marking**

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
06
DIN EN 858-1
separator systems for light liquids Oleopator class II with integrated sludge trap
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD

**Overview of the CE marked separator systems for light liquids  
Type Oleopator**

NS (x)	SF (y)	Oil storage capacity (l)	Ø D (mm)
1,5	150	163	1000
3	300	163	1000
3 TVO	300	512	1000
3	600	163	1000
3 TVO	900	464	1200
4	400	160	1000
4 TVO	400	453	1000
4 TVO	800	512	1200
4	1200	236	1200
4 TVO	1200	576	1500
6	600	160	1000
6 TVO	600	512	1200
6	1200	236	1200
6	1800	576	1500
6	2500	576	1500





**Declaration of Performance** refer to EU BauPVO 305/2011

NS (x)	SF (y)	Oil storage capacity (l)	Ø D (mm)
6	5000	1272	2200
8	800	273	1500
8	1600	576	1500
8-10	1000	273	1200
8	2400	576	1500
10	2000	576	1500
8-10	2500	576	1500
10	3000	576	1500
8-10	5000	1272	2200
15	1500	464	1500
15	3000	464	1500
15	5000	1163	2200
20	2000	594	1500
20	4000	1163	2200
20	5000	1163	2200
20	6000	1163	2200
30	3000	1513	2200
30	5000	1513	2200
30	6000	1513	2200
40	4000	1350	2200
40	5000	1350	2200
50	5000	1350	2200

