



Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/5007		
2 Product description	Separator for light liquids Oleopator CRB		
3 Product specification: (Numbers or Specification of product)	Oleopator CRB NS x (see following page)		
4 Intended use	Light liquid removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
9 First year of CE marking	2006		
10 Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 858-1	Performance
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
06
DIN EN 858-1
separator systems for light liquids Oleopator CRB class I with integrated sludge trap
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD

Overview of the CE marked separator systems for light liquids Type Oleopator CRB

NS (x)	Oil storage capacity (l)	Ø D (mm)
1,5-3	163	1000
4-6	160	1000
8-10	185	1000
15	464	1500
20	594	1500
30	654	1500
40	1350	2200
50	1350	2200
65	1674	2200
80	2216	2200
100	2216	2200

