



## Declaration of Performance refer to EU BauPVO 305/2011

<b>1 DoP Reference number</b>	ST/G1/5009		
<b>2 Product description</b>	Separator for light liquids Oleotop		
<b>3 Product specification: (Numbers or Specification of product)</b>	Oleotop NS x SF y (see following page)		
<b>4 Intended use</b>	Light liquid removal from waste water to protect drainage systems and surface water		
<b>5 Manufacturer</b>	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
<b>6 Authorised representative</b>	Irrelevant		
<b>7 Assessment and verification of constancy of performance</b>	System 3 and System 4		
<b>8 Relevant harmonised standard</b>	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
<b>9 First year of CE marking</b>	2006		
<b>10 Notified body</b>	System 3 – Reaction to fire: NB-Nr. 1508		
<b>11 Type test report reference number</b>	Irrelevant		
<b>12 Essential characteristics</b>	<b>Main features</b>	<b>DIN EN 858-1</b>	<b>Performance</b>
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
<b>13 Specific technical documentation (article 37/38)</b>	Installation manual		
<b>14 Other information</b>	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe  
Managing Director





**Declaration of Performance refer to EU BauPVO 305/2011**

**Information accompanying the CE marking**

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
06
DIN EN 858-1
separator systems for light liquids Oleotop class I with integrated sludge trap
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD

**Overview of the CE marked separator systems for light liquids  
Type Oleotop**

NS (x)	SF (y)	Sludge trap- volume (l)	Oil storage capacity (l)	Ø D (mm)
3	600	300	175	1000
5	1000	500	175	1000
6	1200	600	461	1500
6	2500	1240	461	1500
6	5000	2470	998	2200
8-10	2000	990	998	2200
8-10	3000	1490	998	2200
8-10	5000	2470	998	2200
15	5000	2470	1173	2200
20	5000	2540	1163	2200
30	6000	3035	1094	2670

