



Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/5014		
2 Product description	Separator for light liquids Oleopass		
3 Product specification: (Numbers or Specification of product)	Oleopass NS x SF y (see following page)		
4 Intended use	Light liquid removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
9 First year of CE marking	2006		
10 Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 858-1	Performance
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
	Durability	6.2	pass
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12.
The manufacturer only is responsible for the creation of this declaration of performance according to No. 5.
Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

	
ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt	
06	
DIN EN 858-1	
separator systems for light liquids Oleopass class I with integrated sludge trap	
Material: concrete Installation parts: stainless steel and PE-HD Interior coating: Steopox 246 or interior lining: PE-HD	

Overview of the CE marked separator systems for light liquids Type Oleopass

NS (x)	SF (y)	Oil storage capacity (l)	Size (mm)
6/60	1200	185	1500
8/80	1200	185	1500
8/80	1600	185	1500
10/100	1000	185	1500
10/100	2000	185	1500
15/150	1500	464	2200
15/150	3000	464	2200
20/200	2000	594	2200
20/200	4000	594	2200
30/300	3100	634	2200





Declaration of Performance refer to EU BauPVO 305/2011

NS (x)	SF (y)	Oil storage capacity (l)	Size (mm)
6/60	1600	129	1500
8/80	1600	129	1500
10/100	2500	280	2200
10/100	2500	280	2200
15/150	5000	526	2200
15/150	5000	526	2200
20/160	5000	526	2200
20/160	5000	526	2200