

Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/6001		
2 Product description	Grease separator Lipumax		
Product specification: (Numbers or Specification of product)	Lipumax NS x SF y (see following page)		
4 Intended use	Grease removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 1825-1:2004 + DIN EN 1825-2:2002 + DIN EN 13501-1:2007		
First year of CE marking	2006		
Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 1825-1	Performance
	Reaction to fire	5.2.9	E
	Fluid resistant	5.3.2	pass
	Effectiveness	4, 5.3.1, 5.3.3 – 5.3.10, 5.5	pass
	Capacity	5.4	pass
	Durability	5.2	pass
Specific technical documentation (article 37/38)	Installation manual		
14 Other information	_		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 24th June 2013

Sven Schrothe Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking



ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt

06

DIN EN 1825-1

separator systems for grease Lipumax with integrated sludge trap

Material: concrete Installation parts: PE-HD Interior coating: Tenaxon T 297 HD or interior lining: PE-HD

Overview of the CE marked separator systems for grease Type Lipumax

NS (x)	SF (y)	DN	Ø D (mm)
1	100	100	1000
1-2	200	100	1000
2	400	100	1000
4	400	150	1000
4	800	150	1200
4	800	150	1200
7	700	150	1200
7	1400	150	1500
10	1000	150	1500
10	2000	150	1500
15-20	2000	200	1750
15	3000	200	2200
25	2500	250	2200
25	5000	250	2200

