



Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/6004		
2 Product description	Grease separator Lipumax-P-B, D, DM, D		
3 Product specification: (Numbers or Specification of product)	Lipumax-P-B, D, DM, D NS x SF y (see following page)		
4 Intended use	Grease removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 1825-1:2004 + DIN EN 1825-2:2002 + DIN EN 13501-1:2007		
9 First year of CE marking	2012		
10 Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 1825-1	Performance
	Reaction to fire	5.2.9	E
	Fluid resistant	5.3.2	pass
	Effectiveness	4, 5.3.1, 5.3.3 – 5.3.10, 5.5	pass
	Capacity	5.4	pass
Durability	5.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 24th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
12
DIN EN 1825-1 separator systems for grease Lipumax-P-B, D, DM, D with integrated sludge trap Material: LLDPE Installation parts: PE-HD

Overview of the CE marked separator systems for grease Type Lipumax-P-B, D, DM, D

NS (x)	SF (y)	DN	Ø D (mm)
2	200	100	1320
2	400	100	1320
2/4	400	100	1320
4	800	100	1320
5,5	550	150	1320
5,5	1100	150	1320
7	700	150	1320
8,5	850	150	1320
10	1000	150	1320

