



Declaration of Performance refer to EU BauPVO 305/2011

1 DoP Reference number	ST/G1/6005		
2 Product description	Grease separator Lipumax-PR		
3 Product specification: (Numbers or Specification of product)	Lipumax-PR NS x SF y (see following page)		
4 Intended use	Grease removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
7 Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 1825-1:2004 + DIN EN 1825-2:2002 + DIN EN 13501-1:2007		
9 First year of CE marking	2007		
10 Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
11 Type test report reference number	Irrelevant		
12 Essential characteristics	Main features	DIN EN 1825-1	Performance
	Reaction to fire	5.2.9	E
	Fluid resistant	5.3.2	pass
	Effectiveness	4, 5.3.1, 5.3.3 – 5.3.10, 5.5	pass
	Capacity	5.4	pass
Durability	5.2	pass	
13 Specific technical documentation (article 37/38)	Installation manual		
14 Other information	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 24th June 2013

Sven Schrothe
Managing Director





Declaration of Performance refer to EU BauPVO 305/2011

Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
07
DIN EN 1825-1
separator systems for grease Lipumax-PR with integrated sludge trap
Material: concrete Installation parts: PE-HD Interior coating: Tenaxon T 297 HD or interior lining: PE-HD

Overview of the CE marked separator systems for grease Type Lipumax-PR

NS (x)	SF (y)	DN	Größe (mm)
20	6000	200	5100 x 2500
25	5100	200	5100 x 2500
30	3000	250	5100 x 2500
40	5000	300	5100 x 2500

