

## **Declaration of Performance refer to EU BauPVO 305/2011**

1 DoP Reference number	ST/G1/6006		
2 Product description	Grease separator ECO-FPI new		
Product specification: (Numbers or Specification of product)	ECO-FPI new NS x SF y (see following page)		
4 Intended use	Grease removal from waste water to protect drainage systems and surface water		
5 Manufacturer	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
6 Authorised representative	Irrelevant		
Assessment and verification of constancy of performance	System 3 and System 4		
8 Relevant harmonised standard	DIN EN 1825-1:2004 + DIN EN 1825-2:2002 + DIN EN 13501-1:2007		
9 First year of CE marking	2008		
Notified body	System 3 – Reaction to fire: NB-Nr. 1508		
Type test report reference number	Irrelevant		
	Main features	DIN EN 1825-1	Performance
12 Essential characteristics	Reaction to fire	5.2.9	Е
	Fluid resistant	5.3.2	pass
	Effectiveness	4, 5.3.1, 5.3.3 – 5.3.10, 5.5	pass
	Capacity	5.4	pass
	Durability	5.2	pass
Specific technical documentation (article 37/38)	Installation manual		
14 Other information	_		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12. The manufacturer only is responsible for the creation of this declaration of performance according to No. 5. Signed for and on behalf of the manufacturer.

Bürstadt, 4th June 2013

Sven Schrothe Managing Director





## **Declaration of Performance refer to EU BauPVO 305/2011**

## Information accompanying the CE marking



ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt

80

DIN EN 1825-1

separator systems for grease ECO-FPI new with integrated sludge trap

Material: PE-HD Installation parts: PE-HD

## Overview of the CE marked separator systems for grease Type ECO-FPI new

NS (x)	SF (y)	DN	Ø D (mm)
1	100	100	1000
1	200	100	1000
2	200	100	1000
2	400	100	1000
3	300	100	1000
3	600	100	1000
4	400	100	1000
4	800	100	1000
7	700	150	1500
7	1400	150	1500
10	1000	150	1500
10	2000	150	1500
15	1500	200	2000
15	3000	200	2000
20	2000	200	2000
20	4000	200	2000

